



PDA

PLASTIC DIAL INDICATORS FOR ANCHOR PIN USE



IP65

Original ELESA Model PA11



Housing	Window	Dial Plate	Long Hand	Short Hand
Glass-fiber reinforced polyamide plastic Black matte	Acrylic resin	Aluminum (A1050P)	Red	Black

Part numbers in boldtext are in-stock items, the others are available on request.

Part Number			Rotative Direction	Weight (g)
No. of Graduations 10	No. of Graduations 20	No. of Graduations 30		
PDA50R -1/10	PDA50R -1/20	PDA50R -1/30	Clockwise	80
PDA50L -1/10	PDA50L -1/20	PDA50L -1/30	Counterclockwise	

Display Examples



Type : Clockwise Graduations : 10 Part No. : PDA50R-1/10 Display after 1 revolution	Type : Clockwise Graduations : 20 Part No. : PDA50R-1/20 Display after 3-1/2 revolutions	Type : Counterclockwise Graduations : 30 Part No. : PDA50L-1/3 Display after 11 revolutions
--	---	--

Notes:

- This product is the replacement component for **DGKA** PLASTIC INDICATOR KNURLED KNOBS WITH ANCHOR PIN.
- This indicator cannot be used alone.
- Ensure that Dial Indicators do not receive a hit or shock, which can cause failure in function.

Features:

- Designed to comply with the IP65 protection class.
- This indicator that indicates spindle revolution is suitable with spindles in any position.
- The window is ultrasonically welded to the housing, for excellent splashproof construction.

Technical Information

Working temperature : Between 0°C and 100°C
 These indicators can mount on DGKA PLASTIC INDICATOR KNURLED KNOBS WITH ANCHOR PIN.