




SZ

DIGITAL DIAL INDICATORS



SZ80R-1




Angular Range of Mounting


Housing	Window	Dial	Analog Hand
Glass-fiber reinforced polyamide plastic	Acrylic plastic	Aluminum (A1050P)	Black

Spindle Thread Pitch	Part Number		Display after 1st Revolution	Analog Reading		Weight (g)
	Clockwise	Counterclockwise		Minimal Readable Value	No. of Graduations	
1	SZ80R- 1	SZ80L- 1	00010	0.1	100	180
2	SZ80R- 2	SZ80L- 2	00002		20	
2.5	SZ80R- 2.5	SZ80L- 2.5	00002/5		25	
3	SZ80R- 3	SZ80L- 3	00003		30	
4	SZ80R- 4	SZ80L- 4	00004		40	
5	SZ80R- 5	SZ80L- 5	00005		50	
6	SZ80R- 6	SZ80L- 6	00006		60	
8	SZ80R- 8	SZ80L- 8	00008		80	
10	SZ80R-10	SZ80L-10	00010		100	

Display Examples



Rotative Direction: Clockwise
Spindle Thread Pitch : 2.5
Part Number: SZ80R-2.5
Display after 1 clockwise revolution



Rotative Direction: Counterclockwise
Spindle Thread Pitch : 4
Part Number: SZ80L-4
Display after 2-1/2 counterclockwise revolutions

Features:

- Designed for analog-digital double reading
- Exclusive handwheels (**SHK** **SHKP**) are available in 4 sizes.
- Counterrotating allows counting down the displayed value.

Ordering Example

Product Family Code	Rotative Direction	Spindle Thread Pitch
SZ80	R	8
	L	

R = Clockwise
L = Counterclockwise

- Indicators for special thread pitches are available on request.

Technical Information

For detailed usages, see page of "ALUMINUM INDICATOR HANDWHEELS".